



# PRODUCT SPECIFICATION DRAWING

## HOLDRITE® ProGuard™ #731



HOLDRITE® ProGuard™ #731 "Exploded"



SB4-7312 Shown

Model	Description
731	731 Assy ONLY
SB3-7311	731 (1) & SB3 (1)
SB3-7312	731 (2) & SB3 (1)
SB4-7311	731 (1) & SB4 (1)
SB4-7312	731 (2) & SB4 (1)

**The HOLDRITE® ProGuard™ #731 supports 1/2" PEX Tubing, CPVC, Copper & Copper Bullets. The HOLDRITE® ProGuard™ #731 is for use with #SB3 & #SB4 brackets only.**

### Product Information:

- Material: PVC, White, UL94V-0  
Nylon 6/6, Purple, UL94V-0
- Temperature range: -10 °F to +140 °F
- Load rating: 25 pounds
- UPC / IAPMO listed



THIS INFORMATION IS PROPRIETARY TO HOLDRITE AND IS SUBJECT TO CHANGE WITHOUT NOTICE. IT MAY NOT BE REPRODUCED IN PART OR WHOLE WITHOUT WRITTEN AUTHORIZATION.

# HOLDRITE®

CONVERTING MAKESHIFT METHODS INTO ENGINEERED SOLUTIONS<sup>SM</sup>

800-321-0316 OR 760-744-6944 / FAX: 760-744-0507 / WWW.HOLDRITE.COM  
spec\_731\_RevD

Product Submittal	
Job Name:	
Date:	
Part Number:	Qty:
Architect / Owner:	
Contractor:	
Notes:	