




HOLDRITE Silencer[™] Standard Clamps

#266 | #267 #268 | #269



KEY FEATURES AND BENEFITS:

- Noise and Vibration Isolation Supports
- Field tested and proven
- Compatible with copper, PEX, CPVC, cast iron, and other pipe materials
- Supports ½" through 1 ¼" pipe
- ✓ Integrates with HOLDRITE Stout Bracket® pipe support brackets

- Acoustic noise reduction data available
- Framework meets UL 94 V-2 flame rating
- IAPMO UPC/IPC Listed
- Specifications available at www.HOLDRITE.com
- HOLDRITE Silencer clamps are recognized by their blue and white coloring

HOLDRITE® Silencer™ | 269 Isolator | 1 ¼"

STANDARD SIZES AVAILABLE:











HOLDRITE Silencer[™] **Standard Clamps**

#266 | #267 | #268 | #269

PRODUCT INFORMATION:

Material:


Shell: Polypropylene, blue, FR UL94-V2


Isolators: TPR, natural (off-white), 40 to 45 shore A **Temperature Range:** -10 F to 140 F (suspension)


Load Rating: 25 pounds in suspension mode

IAPMO UPC / IPC listed

IAPMO listed, per standard PS42-2013








PRODUCT SPECIFICATION DRAWINGS HOLDRITE® #266 - #269

Model #'s 266 thru 269 can be used as a top mount or suspension hanger, e.g., from a joist or cross-member, or from a HOLDRITE Stout Bracket[®]. These models are used for securing and retaining tubing while providing superior acoustical isolation between the tubing and the supporting structure. Supports 1/2", 3/4", 1" & 1-1/4" CTS tube sizes. Supports Copper, PEX, CPVC tubing, conduit, etc. UPC listed.

Model	Size	A	В	С	D	E	F
#266	1/2"	2.13	1.75	1.00	1.17	.62	.62
#267	3/4"	2.5	1.93	1.00	1.55	.81	.87
#268	1"	2.75	2.27	1.45	1.82	.94	1.12
#269	1 1/4"	2.88	2.50	1.45	2.07	1.07	1.36





HORIZONTAL / VERTICAL PIPING SHOWN WITH HOLDRITE®

#266 thru #269 Acoustical Clamps. Mounted On HOLDRITE Stout Bracket® #SB2 & #SB3. Clamps Support 1/2", 3/4", 1" & 1-1/4" CTS Tube Sizes.