PRODUCT SPECIFICATION DRAWING HOLDRITE® #114-COH Supports flush valves on carriers 2.50 .50 4 3/4" EXTRUDED THROUGH FOR 1" COPPER PIPE. Ø.19 NAIL HOLES SLOTS & HOLES = 23.25 21,50 **CLEARANCE FOR** 5/8" BOLTS. 26 1/2" 6 7.50 3.88 2.25 .75 .68 1.12

ALL DIMENSIONS IN INCHES

This heavy-gage Copper-Bonded[™] #114-COH offset carrier bracket mounts directly to a 4-bolt siphon jet closet carrier and positions the flush valve at 11 1/2" above the fixture, and offsets it 4-3/4" from the center of the carrier. "Figure 8" hole pattern on top provides 1/4" left or right offset for flush valve support providing a single bracket to be used in a left or right hand installation while providing the desired 4-3/4" center line rough-in. The hinged top assembly allows for placement of a pre-capped 1" copper stub out. When soldering, heat the pipe, not the bracket.

Product Information:

- Material: 16 gage CRS, Copper-Bonded™
- Works with all 4 bolt carriers
- Unique flush valve support hole accommodates a 4-3/4" center line rough-in
- Includes 1/2" holes for positioning various trap primers
- Works with current #114-C-EXT bracket

Product Submittal	
Job Name:	
Date:	
Part Number:	Qty:
Architect / Owner:	
Contractor:	
Notes:	



THIS INFORMATION IS PROPRIETARY TO HOLDRITE AND IS SUBJECT TO CHANGE WITHOUT NOTICE. IT MAY NOT BE REPRODUCED IN PART OR WHOLE WITHOUT WRITTEN AUTHORIZATION.